

## Dual Magnet Mount Surface Thermometers





Dual Magnet
Surface Thermometer



Dual Magnet
Surface Thermometer
With Ancillary Hand



Dual Magnet
Surface Thermometer
With Max-Min Hands



Dual Magnet
Surface Thermometer
Dual Scale F & C

- PTC® Quality Made in the U.S.A.
- NIST Certification Available
- Accuracy of ±2% of Full Scale Range
- Each Instrument is Individually Calibrated
- Available in Celsius, Fahrenheit or Dual Scale
- Also Available in Tab Mount (no magnets)



Tab Mount Surface
Thermometer (no magnets)



Dual Magnet Surface
Thermometer Back View

SPECIFICATIONS		
Time Constant	0.6 to 1 Minute	
Accuracy	±2% of Full Range	
Diameter	2 in (5.1cm)	
Height	0.5 in. (1.3 cm)	
Weight	1 1/2 oz (43 g)	
Shipping Weight	1 lb. (454 g)	

THE best bimetal surface thermometer on the market for over sixty years. PTC®'s surface thermometers are unrivaled for their combination of accuracy, quality, versatility, and economy. Manufactured from the finest materials, these instruments will continue to give accurate readings for many years. Each thermometer is individually calibrated and serialized. Our thermometers have an accuracy of ±2% of full scale range and are backed by a one year warranty. Certification service using NIST traceable standards and in accordance with ANSI/NCSL Z540-1 is available for all of these units.

## **ISO 17025 ACCREDITED LABORATORY**

Model	Range	Divisions
312C	-20°C to 120°C	1°C
312F	0°F to 250°F	2°F
313C	-20°C to 250°C	2°C
313F	0°F to 500°F	5°F
314C	10°C to 400°C	5°C
314F	50°F to 750°F	10°F
315C	-15°C to 65°C	1°C
315F	0°F to 150°F	1°F
330C	-70°C to 70°C	2°C
330F	-100°F to 160°F	2°F