

SENSIT[®] CO
CARBON MONOXIDE ANALYZER



Easily test ambient air and flue gas samples for Carbon Monoxide.

MADE IN USA

Find Quality Products Online at:



Innovative Detection Solutions

www.GlobalTestSupply.com

sales@GlobalTestSupply.com

SENSIT[®] CO

Use **SENSIT[®] CO** for Carbon Monoxide testing in residential and commercial buildings.

SENSIT[®] CO is perfect for testing ambient air and flue gas samples. The instrument features a powerful pump, hot air probe and bright LCD display.

SENSIT[®] CO is available with an oxygen sensing feature. When so equipped, the instrument will simultaneously display CO and O₂ readings for thorough flue gas testing. Ask for the **SENSIT[®] CO PLUS**.

An infrared communication window allows you to easily print test results to an accessory printer or transfer the data to PC.

SENSIT[®] CO is

- Accurate
- Durable
- Easy to Use
- Easy to Maintain
- Made in USA



Standard Features

- Internal Pump
- Flue Probe with Water Trap
- Audible/Visual Alarms
- Backlit LCD Display
- Automatic Zeroing
- Field Calibration
- Calibration Alerts
- Memory Storage
- Infrared Download
- Hard Carrying Case



Applications

- CO Investigations
- Flue Gas Testing
- Equipment Inspection & Testing





Patented

TO OPERATE:

1. Press Power
2. Wait 45 Seconds for Automatic Zeroing
3. Begin to Use



STANDARD KIT

- Hard Carrying Case
- 3 "C" Batteries
- Flue Probe
- 5 Foot Flexible Tubing
- Particle Filter
- Wrist Strap
- Instruction Manual

OPTIONAL FEATURES

- Oxygen Sensing:**
Display Oxygen and CO Simultaneously
- Air-Free CO Reading:**
Automatically Calculates CO Based on Air-Free Calculation

SENSOR SPECIFICATIONS

| TYPE | RESOLUTION | RANGE | ACCURACY |
|----------------|------------|-------------|----------------|
| CO | 1ppm | 0-2,000 ppm | ±5ppm or 5%** |
| CO "Air Free"* | 1ppm | 0-5,000 ppm | ±5ppm or 5%** |
| O2* | 0.1% | 0-25% | ±0.2% or 10%** |

*Optional Configuration

**Whichever is greater

PRODUCT SPECIFICATIONS

- Size: 3" x 10" x 2.4" (7.6 x 25.4 x 6cm)
- Weight: 1.1 pounds (0.5kg)
- Operational Temp: -4 to 104 F (-20 to 40° C)
- Battery Life: Alkaline: Approximately 30 hrs. Continuous



SENSIT® CO instruments are approved UL913, For Class I, Division 1, Groups C and D hazardous locations when used with Duracell MN1400BK or equivalent alkaline batteries.

SENSIT® CO Instruments

SENSIT CO
Part # 913-00000-04

SENSIT CO with Calibration Kit
Part # 913-00000-05

SENSIT CO plus (carbon monoxide and oxygen)
Part # 913-00000-10

SENSIT® CO Standard Kit Replacement Parts

Hard Carrying Case
Part # 872-00001

Hot Air Probe (Flue Gas)
Part # 883-00023

Dirt and Water Filter Assembly (Particle Filter)
Part # 873-00005

Replacement Cartridge for Filter Assembly
Part # 873-00008

Wrist Strap
Part # 360-00040

Instruction Manual
Part # 750-00013

SENSIT® CO Manual Calibration Kits

Sensit CO Calibration Kit (21 liter 100ppm CO/Air)
Part # 881-00022

SENSIT® CO Replacement Cylinders

21 liter 100ppm CO/Air
Part # 315-080006

221 liter 100ppm CO/Air
Part # 315-180005

SENSIT® CO Automated Calibration

SMART-CAL Auto Calibration Station Only
Part # 914-00000-01

Contact SENSIT to discuss calibration kit for Smart-Cal



MADE IN USA

SENSIT Technologies
is in compliance with ISO 9001:2008

