

## EMF450 Multi-Field **EMF Meter**



Convenient 3-in-1 EMF meter simultaneously measures and displays Magnetic Field, Electric Field, and Radio Frequency Strength. Ergonomic pocket-sized design with an easy-to-navigate menu. Large vivid color TFT display shows digital readings, bargraphs, and trending graph.

## Applications:

- Home appliances
- Power lines,
- Electrical appliances
- Industrial devices
- Mobile/cell phones
- Base stations



## **Features**

- Multi-Field measurements: Magnetic Field, Electric Field, and Radio Frequency (RF) Strength
- Magnetic Field Triple Axis Sensor (X, Y, Z)
- Audible alarm
- 2.4" (240 x 320 pixels) color TFT display
- Adjustable screen brightness (low, medium, high)
- Store up to 20 RF historical records
- · Data Hold and Auto Power Off with disable feature
- Five languages: English, Traditional/Simplified Chinese, Japanese, Spanish
- Complete with 3 AAA batteries

Specifications	Range	Max Resolution	Basic Accuracy
Magnetic Fields (50/60Hz)	20/200/2000mG	0.02/0.1/1mG	±(15%+100 digit)
	2/20/200µT	0.02/0.1/1µT	
Electric Fields (50/60Hz)	50V/m to 2000V/m		$\pm (7\% + 50dgt)$
RF Strength (50MHz to 3.5GHz)	0.02uW/m² to 554.6mW/m²	0.02μW/m²	
	0.02uW/cm <sup>2</sup> to 55.4uW/cm <sup>2</sup>	0.002µW/cm²	
	36.1mV/m to14.46V/m	0.2mV/m	
	0.02mA/m to 38.35mA/m	0.2μA/m	
	-51dB to 16dBm	2dB	±2dB at 2.45GHz
Dimensions/ Weight	4.5 x 2.4 x 0.8" (115 x 60 x 21mm)/ 4.2oz (120g)		
Bargraph	Magnetic Fields	RF Strength	Electric Field
Green	0 to 10.00mG	0 to 0.99mW/m <sup>2</sup>	0 to 500V/m
		0 to 0.59V/m	
Yellow	10.01 to 100mG	1 to 9.99mW/m <sup>2</sup>	501 to 1000V/m
		0.6 to 1.9V/m	
Red	101 to 2000mG	>10mW/m <sup>2</sup>	>1001V/m
		>2V/m	

## **Ordering**

EMF450 ..... Multi-Field EMF Meter

 $(\epsilon$ 

UPC Code: 793950224502

Specifications subject to change without notice. Copyright © 2015-2016 FLIR Systems, Inc. All rights reserved including the right of reproduction in whole or in part in any form.

www.extech.com